

Product Name: MOBIL DELVAC EXTENDED LIFE 50/50 PREDILUTED COOLANT/ANTIFREEZE  
Revision Date: 13 May 2020  
Page 1 of 11

## SAFETY DATA SHEET

### SECTION 1

#### PRODUCT AND COMPANY IDENTIFICATION

##### PRODUCT

Product Name: MOBIL DELVAC EXTENDED LIFE 50/50 PREDILUTED COOLANT/ANTIFREEZE  
Product Description: Glycol  
Product Code: 351010101596, 840439-00, 97AA97  
Intended Use: Antifreeze/coolant

##### COMPANY IDENTIFICATION

###### Supplier:

EXXON MOBIL CORPORATION  
22777 Springwoods Village Parkway  
Spring, TX 77389 USA

24 Hour Health Emergency  
Transportation Emergency Phone  
Product Technical Information  
MSDS Internet Address

609-737-4411  
800-424-9300 or 703-527-3887 CHEMTREC  
800-662-4525  
www.exxon.com, www.mobil.com

### SECTION 2

#### HAZARDS IDENTIFICATION

This material is hazardous according to regulatory guidelines (see (M)SDS Section 15).

##### CLASSIFICATION:

Acute oral toxicant: Category 4. Reproductive toxicant (fertility): Category 1B. Specific target organ toxicant (repeated exposure): Category 1.

##### LABEL:

###### Pictogram:



Signal Word: Danger

##### Hazard Statements:

H302: Harmful if swallowed. H360: May damage fertility. H372: Causes damage to organs through prolonged or repeated exposure. H373: May cause damage to organs through prolonged or repeated exposure. Kidney

##### Precautionary Statements:

P101: If medical advice is needed, have product container or label at hand. P102: Keep out of reach of children.  
P103: Read label before use. P201: Obtain special instructions before use. P202: Do not handle until all safety precautions have been read and understood. P260: Do not breathe mist / vapours. P264: Wash skin thoroughly after handling. P270: Do not eat, drink or smoke when using this product. P280: Wear protective gloves and



Product Name: MOBIL DELVAC EXTENDED LIFE 50/50 PREDILUTED COOLANT/ANTIFREEZE  
Revision Date: 13 May 2020  
Page 2 of 11

clothing, P301 + P310: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. P315: Get immediate medical advice/attention. P308 + P313: IF exposed or concerned: Get medical advice/attention. P314: Get medical advice/attention if you feel unwell. P330: Rinse mouth. P405: Store locked up. P501: Dispose of contents and container in accordance with local regulations.

**Contains:** DIETHYLENE GLYCOL; ETHYLENE GLYCOL; POTASSIUM P-TERT-BUTYL-BENZOATE

**Other hazard information:**

**HAZARD NOT OTHERWISE CLASSIFIED (HNOC):** None as defined under 29 CFR 1910.1200.

**PHYSICAL / CHEMICAL HAZARDS**  
No significant hazards.

**HEALTH HAZARDS**  
High-pressure injection under skin may cause serious damage. Ingestion may cause serious adverse effects and may be fatal. May cause kidney failure and central nervous system effects. Prolonged exposure to elevated concentrations of mist or liquid may cause irritation of the skin, eyes, and respiratory tract.

**ENVIRONMENTAL HAZARDS**  
No significant hazards.

|                        |            |                 |               |
|------------------------|------------|-----------------|---------------|
| <b>NFPA Hazard ID:</b> | Health: 1  | Flammability: 1 | Reactivity: 0 |
| <b>HMIS Hazard ID:</b> | Health: 2* | Flammability: 1 | Reactivity: 0 |

**NOTE:** This material should not be used for any other purpose than the intended use in Section 1 without expert advice. Health studies have shown that chemical exposure may cause potential human health risks which may vary from person to person.

### SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

This material is defined as a mixture.

**Hazardous Substance(s) or Complex Substance(s) required for disclosure**

| Name                            | CAS#       | Concentration* | GHS Hazard Codes                    |
|---------------------------------|------------|----------------|-------------------------------------|
| DIETHYLENE GLYCOL               | 111-46-6   | 1 - < 5%       | H302                                |
| ETHYLENE GLYCOL                 | 107-21-1   | 40 - < 50%     | H302, H373                          |
| POTASSIUM P-TERT-BUTYL-BENZOATE | 16518-26-6 | 1 - < 2.5%     | H302, H360(1B)(F), H372, H401, H411 |

\* All concentrations are percent by weight unless material is a gas. Gas concentrations are in percent by volume.

As per paragraph (i) of 29 CFR 1910.1200, formulation is considered a trade secret and specific chemical identity and exact percentage (concentration) of composition may have been withheld. Specific chemical identity and exact percentage composition will be provided to health professionals, employees, or designated representatives in accordance with applicable provisions of paragraph (i).

### SECTION 4 FIRST AID MEASURES



Product Name: MOBIL DELVAC EXTENDED LIFE 50/50 PREDILUTED COOLANT/ANTIFREEZE  
Revision Date: 13 May 2020  
Page 3 of 11

## INHALATION

Immediately remove from further exposure. Get immediate medical assistance. For those providing assistance, avoid exposure to yourself or others. Use adequate respiratory protection. Give supplemental oxygen, if available. If breathing has stopped, assist ventilation with a mechanical device.

## SKIN CONTACT

Wash contact areas with soap and water. If product is injected into or under the skin, or into any part of the body, regardless of the appearance of the wound or its size, the individual should be evaluated immediately by a physician as a surgical emergency. Even though initial symptoms from high pressure injection may be minimal or absent, early surgical treatment within the first few hours may significantly reduce the ultimate extent of injury.

## EYE CONTACT

Flush thoroughly with water. If irritation occurs, get medical assistance.

## INGESTION

Seek immediate medical attention.

## NOTE TO PHYSICIAN

This product contains ethylene glycol and/or diethylene glycol which, if ingested, are metabolized to toxic metabolites by the enzyme alcohol dehydrogenase, for which ethanol and 4-methylpyrazole {U.S. drug name Fomepizole, trade name Antizol} are antagonists. Administration of oral or intravenous ethanol or intravenous 4-methylpyrazole may arrest further metabolism of this material and thereby ameliorate the toxicity. Use of ethanol or 4-methylpyrazole does not affect toxic metabolites that are already present and is not a substitute for hemodialysis.

## SECTION 5

### FIRE FIGHTING MEASURES

#### EXTINGUISHING MEDIA

**Appropriate Extinguishing Media:** Use water fog, alcohol-resistant foam, dry chemical or carbon dioxide (CO<sub>2</sub>) to extinguish flames.

**Inappropriate Extinguishing Media:** Straight Streams of Water or Regular Foam

#### FIRE FIGHTING

**Fire Fighting Instructions:** Material will not burn. Prevent runoff from fire control or dilution from entering streams, sewers, or drinking water supply.

**Unusual Fire Hazards:** Hazardous material. Firefighters should consider protective equipment indicated in Section 8.

**Hazardous Combustion Products:** Aldehydes, Incomplete combustion products, Oxides of carbon, Smoke, Fume

#### FLAMMABILITY PROPERTIES

**Flash Point [Method]:** N/A

**Flammable Limits (Approximate volume % in air):** LEL: N/D UEL: N/D

**Autoignition Temperature:** >400°C (752°F)

## SECTION 6

### ACCIDENTAL RELEASE MEASURES



## NOTIFICATION PROCEDURES

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations. US regulations require reporting releases of this material to the environment which exceed the applicable reportable quantity or oil spills which could reach any waterway including intermittent dry creeks. The National Response Center can be reached at (800)424-8802.

## PROTECTIVE MEASURES

Avoid contact with spilled material. Warn or evacuate occupants in surrounding and downwind areas if required due to toxicity or flammability of the material. See Section 5 for fire fighting information. See the Hazard Identification Section for Significant Hazards. See Section 4 for First Aid Advice. See Section 8 for advice on the minimum requirements for personal protective equipment. Additional protective measures may be necessary, depending on the specific circumstances and/or the expert judgment of the emergency responders.

## SPILL MANAGEMENT

**Land Spill:** Stop leak if you can do it without risk. Do not touch or walk through spilled material. Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Recover by pumping or with suitable absorbent.

**Water Spill:** Stop leak if you can do it without risk. Consult an expert. Warn other shipping. Material will sink. Remove material, as much as possible, using mechanical equipment.

Water spill and land spill recommendations are based on the most likely spill scenario for this material; however, geographic conditions, wind, temperature, (and in the case of a water spill) wave and current direction and speed may greatly influence the appropriate action to be taken. For this reason, local experts should be consulted. Note: Local regulations may prescribe or limit action to be taken.

## ENVIRONMENTAL PRECAUTIONS

Remove debris in path of spill and remove contaminated debris from shoreline and water surface and dispose of according to local regulations. Large Spills: Dike far ahead of liquid spill for later recovery and disposal. Prevent entry into waterways, sewers, basements or confined areas.

## SECTION 7

### HANDLING AND STORAGE

#### HANDLING

Avoid breathing mists or vapors. Avoid contact with skin. Prevent small spills and leakage to avoid slip hazard.

**Static Accumulator:** This material is not a static accumulator.

#### STORAGE

Do not store in open or unlabelled containers.

## SECTION 8

### EXPOSURE CONTROLS / PERSONAL PROTECTION

#### EXPOSURE LIMIT VALUES

Exposure limits/standards (Note: Exposure limits are not additive)



| Substance Name    | Form                  | Limit / Standard |                      |  | NOTE | Source       |
|-------------------|-----------------------|------------------|----------------------|--|------|--------------|
|                   |                       |                  |                      |  |      |              |
| DIETHYLENE GLYCOL |                       | TWA              | 10 mg/m <sup>3</sup> |  | N/A  | OARS<br>WEEL |
| ETHYLENE GLYCOL   | Aerosol,<br>Inhalable | STEL             | 10 mg/m <sup>3</sup> |  | N/A  | ACGIH        |
| ETHYLENE GLYCOL   | Vapor fraction        | STEL             | 50 ppm               |  | N/A  | ACGIH        |
| ETHYLENE GLYCOL   | Vapor fraction        | TWA              | 25 ppm               |  | N/A  | ACGIH        |

NOTE: Limits/standards shown for guidance only. Follow applicable regulations.

No biological limits allocated.

## ENGINEERING CONTROLS

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Control measures to consider:

No special requirements under ordinary conditions of use and with adequate ventilation.

## PERSONAL PROTECTION

Personal protective equipment selections vary based on potential exposure conditions such as applications, handling practices, concentration and ventilation. Information on the selection of protective equipment for use with this material, as provided below, is based upon intended, normal usage.

**Respiratory Protection:** If engineering controls do not maintain airborne contaminant concentrations at a level which is adequate to protect worker health, an approved respirator may be appropriate. Respirator selection, use, and maintenance must be in accordance with regulatory requirements, if applicable. Types of respirators to be considered for this material include:

No protection is ordinarily required under normal conditions of use and with adequate ventilation.

For high airborne concentrations, use an approved supplied-air respirator, operated in positive pressure mode. Supplied air respirators with an escape bottle may be appropriate when oxygen levels are inadequate, gas/vapor warning properties are poor, or if air purifying filter capacity/rating may be exceeded.

**Hand Protection:** Any specific glove information provided is based on published literature and glove manufacturer data. Glove suitability and breakthrough time will differ depending on the specific use conditions. Contact the glove manufacturer for specific advice on glove selection and breakthrough times for your use conditions. Inspect and replace worn or damaged gloves. The types of gloves to be considered for this material include:

Chemical resistant gloves are recommended. If contact with forearms is likely wear gauntlet style gloves.

**Eye Protection:** If contact is likely, safety glasses with side shields are recommended.

**Skin and Body Protection:** Any specific clothing information provided is based on published literature or manufacturer data. The types of clothing to be considered for this material include:

Chemical/oil resistant clothing is recommended.

**Specific Hygiene Measures:** Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and



protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

## ENVIRONMENTAL CONTROLS

Comply with applicable environmental regulations limiting discharge to air, water and soil. Protect the environment by applying appropriate control measures to prevent or limit emissions.

## SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Note: Physical and chemical properties are provided for safety, health and environmental considerations only and may not fully represent product specifications. Contact the Supplier for additional information.

### GENERAL INFORMATION

Physical State: Liquid  
Color: Red  
Odor: Characteristic  
Odor Threshold: N/D

### IMPORTANT HEALTH, SAFETY, AND ENVIRONMENTAL INFORMATION

Relative Density (at 15 °C): 1.07  
Flammability (Solid, Gas): N/A  
Flash Point [Method]: N/A  
Flammable Limits (Approximate volume % in air): LEL: N/D UEL: N/D  
Autoignition Temperature: >400°C (752°F)  
Boiling Point / Range: 106°C (223°F) - 108°C (226°F)  
Decomposition Temperature: N/D  
Vapor Density (Air = 1): 2.1 at 101 kPa [n-Butyl Acetate]  
Vapor Pressure: < 0.013 kPa (0.1 mm Hg) at 20 °C  
Evaporation Rate (n-butyl acetate = 1): N/D  
pH: 8.6  
Log Pow (n-Octanol/Water Partition Coefficient): < 2  
Solubility in Water: Complete  
Viscosity: <15.6 cSt (15.6 mm<sup>2</sup>/sec) at 40 °C  
Oxidizing Properties: See Hazards Identification Section.

### OTHER INFORMATION

Freezing Point: -37°C (-35°F)  
Melting Point: N/D

## SECTION 10 STABILITY AND REACTIVITY

REACTIVITY: See sub-sections below.

STABILITY: Material is stable under normal conditions.

CONDITIONS TO AVOID: High energy sources of ignition.

MATERIALS TO AVOID: Strong Acids, Strong oxidizers



**HAZARDOUS DECOMPOSITION PRODUCTS:** Material does not decompose at ambient temperatures.

**POSSIBILITY OF HAZARDOUS REACTIONS:** Hazardous polymerization will not occur.

**SECTION 11 TOXICOLOGICAL INFORMATION**

**INFORMATION ON TOXICOLOGICAL EFFECTS**

| Hazard Class   | Conclusion / Remarks   |
|--|--|
| <b>Inhalation</b>  |  |
| Acute Toxicity: No end point data for material.                | Minimally Toxic. Based on assessment of the components.  |
| Irritation: No end point data for material.                    | Negligible hazard at ambient/normal handling temperatures.   |
| <b>Ingestion</b>   |  |
| Acute Toxicity (Human): LDLo 100 ml                            | Moderately toxic. Based on assessment of the components.   |
| <b>Skin</b>  |  |
| Acute Toxicity: No end point data for material.                | Minimally Toxic. Based on assessment of the components.  |
| Skin Corrosion/Irritation: No end point data for material.     | Negligible irritation to skin at ambient temperatures. Based on assessment of the components.                                      |
| <b>Eye</b>   |  |
| Serious Eye Damage/Irritation: No end point data for material. | May cause mild, short-lasting discomfort to eyes. Based on assessment of the components.   |
| <b>Sensitization</b>   |  |
| Respiratory Sensitization: No end point data for material.     | Not expected to be a respiratory sensitizer.   |
| Skin Sensitization: No end point data for material.            | Not expected to be a skin sensitizer. Based on assessment of the components.   |
| <b>Aspiration:</b> Data available.                             | Not expected to be an aspiration hazard. Based on physico-chemical properties of the material.                                     |
| <b>Germ Cell Mutagenicity:</b> No end point data for material. | Not expected to be a germ cell mutagen. Based on assessment of the components.   |
| <b>Carcinogenicity:</b> No end point data for material.        | Not expected to cause cancer. Based on assessment of the components.   |
| <b>Reproductive Toxicity:</b> No end point data for material.  | Caused damage to fertility in laboratory animals, but the relevance to humans is uncertain. Based on assessment of the components. |
| <b>Lactation:</b> No end point data for material.              | Not expected to cause harm to breast-fed children.   |
| <b>Specific Target Organ Toxicity (STOT)</b>                   |  |
| Single Exposure: No end point data for material.               | Not expected to cause organ damage from a single exposure.   |
| Repeated Exposure: No end point data for material.             | Concentrated, prolonged or deliberate exposure may cause organ damage. Based on assessment of the components.                      |

**OTHER INFORMATION**

**For the product itself:**

Target Organs Repeated Exposure: Kidney

**Contains:**

**DIETHYLENE GLYCOL (DEG):** Orally, DEG is more toxic to humans than animal test data indicate. Probable lethal dose for an adult is about 50 ml (2 oz.), or 2 -3 swallows. Smaller amounts may cause kidney degeneration and failure. Benign urinary bladder tumors were observed in rats, no tumors were observed in mice.

**ETHYLENE GLYCOL (EG):** Repeated high oral exposure has caused kidney damage, neurological effects,



degeneration of the liver and changes in blood chemistry and circulating blood cells in laboratory animals. Repeated overexposure has the potential to cause similar toxic effects in humans. EG causes developmental and reproductive effects at high dose levels in laboratory animals. The relevance of these findings to humans is uncertain.

The following ingredients are cited on the lists below: None.

1 = NTP CARC  
2 = NTP SUS

--REGULATORY LISTS SEARCHED--

3 = IARC 1  
4 = IARC 2A

5 = IARC 2B  
6 = OSHA CARC

## SECTION 12

### ECOLOGICAL INFORMATION

The information given is based on data for the material, components of the material, or for similar materials, through the application of bridging principals.

#### ECOTOXICITY

Material -- Not expected to be harmful to aquatic organisms.

#### MOBILITY

Material -- Expected to remain in water or migrate through soil.

#### PERSISTENCE AND DEGRADABILITY

##### Biodegradation:

Material -- Expected to be readily biodegradable.

##### Atmospheric Oxidation:

Material -- Expected to degrade rapidly in air

#### BIOACCUMULATION POTENTIAL

Material -- Potential to bioaccumulate is low.

## SECTION 13

### DISPOSAL CONSIDERATIONS

Disposal recommendations based on material as supplied. Disposal must be in accordance with current applicable laws and regulations, and material characteristics at time of disposal.

#### DISPOSAL RECOMMENDATIONS

Even though this product is biodegradable, it must not be indiscriminately discarded into the environment. Product is suitable for burning in an enclosed controlled burner for fuel value or disposal by supervised incineration at very high temperatures to prevent formation of undesirable combustion products.

#### REGULATORY DISPOSAL INFORMATION

RCRA Information: The unused product, in our opinion, is not specifically listed by the EPA as a hazardous waste (40 CFR, Part 261D), nor is it formulated to contain materials which are listed as hazardous wastes. It does not exhibit the hazardous characteristics of ignitability, corrosivity or reactivity and is not formulated with contaminants as determined by the Toxicity Characteristic Leaching Procedure (TCLP). However, used product may be regulated.



Product Name: MOBIL DELVAC EXTENDED LIFE 50/50 PREDILUTED COOLANT/ANTIFREEZE  
Revision Date: 13 May 2020  
Page 9 of 11

**Empty Container Warning** Empty Container Warning (where applicable): Empty containers may contain residue and can be dangerous. Do not attempt to refill or clean containers without proper instructions. Empty drums should be completely drained and safely stored until appropriately reconditioned or disposed. Empty containers should be taken for recycling, recovery, or disposal through suitably qualified or licensed contractor and in accordance with governmental regulations. DO NOT PRESSURISE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION. THEY MAY EXPLODE AND CAUSE INJURY OR DEATH.

**SECTION 14 TRANSPORT INFORMATION**

**LAND (DOT)**

**Proper Shipping Name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCES, LIQUID, N.O.S. (Ethylene Glycol)  
**Hazard Class & Division:** 9  
**ID Number:** 3082  
**Packing Group:** III  
**Product RQ:** 10000 LBS - ETHYLENE GLYCOL  
**ERG Number:** 171  
**Label(s):** 9  
**Transport Document Name:** UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCES, LIQUID, N.O.S. (Ethylene Glycol), 9, PG III, RQ

Footnote: This material is not regulated under 49 CFR when the quantity in a package is less than the Product RQ.

**LAND (TDG):** Not Regulated for Land Transport

**SEA (IMDG):** Not Regulated for Sea Transport according to IMDG-Code

**Marine Pollutant:** No

**AIR (IATA):** Not Regulated for Air Transport  
, EHS

**SECTION 15 REGULATORY INFORMATION**

**OSHA HAZARD COMMUNICATION STANDARD:** This material is considered hazardous in accordance with OSHA HazCom 2012, 29 CFR 1910.1200.

**Listed or exempt from listing/notification on the following chemical inventories:** DSL, TSCA

**SARA 302:** No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302

**CERCLA:**

| Chemical Name   | CAS Number | Typical Value | Component RQ | Product RQ |
|-----------------|------------|---------------|--------------|------------|
| ETHYLENE GLYCOL | 107-21-1   | 40 - < 50%    | 5000 LBS     | 10000 LBS  |



Product Name: MOBIL DELVAC EXTENDED LIFE 50/50 PREDILUTED COOLANT/ANTIFREEZE  
 Revision Date: 13 May 2020  
 Page 10 of 11

**SARA (311/312) REPORTABLE GHS HAZARD CLASSES:** Acute Toxicity (any route of exposure), Reproductive toxicity, Specific Target Organ toxicity (single or repeated exposure)

**SARA (313) TOXIC RELEASE INVENTORY:**

| Chemical Name   | CAS Number | Typical Value |
|-----------------|------------|---------------|
| ETHYLENE GLYCOL | 107-21-1   | 40 - < 50%    |

The following ingredients are cited on the lists below:


| Chemical Name     | CAS Number | List Citations        |
|-------------------|------------|-----------------------|
| DIETHYLENE GLYCOL | 111-46-6   | 16                    |
| ETHYLENE GLYCOL   | 107-21-1   | 1, 11, 13, 16, 18, 19 |

--REGULATORY LISTS SEARCHED--

- |               |                  |                   |             |
|---------------|------------------|-------------------|-------------|
| 1 = ACGIH ALL | 6 = TSCA 5a2     | 11 = CA P65 REPRO | 16 = MN RTK |
| 2 = ACGIH A1  | 7 = TSCA 5e      | 12 = CA RTK       | 17 = NJ RTK |
| 3 = ACGIH A2  | 8 = TSCA 6       | 13 = IL RTK       | 18 = PA RTK |
| 4 = OSHA Z    | 9 = TSCA 12b     | 14 = LA RTK       | 19 = RI RTK |
| 5 = TSCA 4    | 10 = CA P65 CARC | 15 = MI 293       |             |

Code key: CARC=Carcinogen; REPRO=Reproductive

**SECTION 16 OTHER INFORMATION**

 **WARNING:** Reproductive Harm - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

This warning is given to comply with California Health and Safety Code 25249.6 and does not constitute an admission or a waiver of rights.

N/D = Not determined, N/A = Not applicable

**KEY TO THE H-CODES CONTAINED IN SECTION 3 OF THIS DOCUMENT (for information only):**

- H302: Harmful if swallowed; Acute Tox Oral, Cat 4
- H360(1B)(F): May damage fertility; Repro Tox, Cat 1B (Fertility)
- H372: Causes damage to organs through prolonged or repeated exposure; Target Organ, Repeated, Cat 1
- H373: May cause damage to organs through prolonged or repeated exposure; Target Organ, Repeated, Cat 2
- H401: Toxic to aquatic life; Acute Env Tox, Cat 2
- H411: Toxic to aquatic life with long lasting effects; Chronic Env Tox, Cat 2

**THIS SAFETY DATA SHEET CONTAINS THE FOLLOWING REVISIONS:**

- GHS Health Symbol information was modified.
- Section 09: Autoignition Temperature information was modified.

The information and recommendations contained herein are, to the best of ExxonMobil's knowledge and belief, accurate and reliable as of the date issued. You can contact ExxonMobil to insure that this document is the most current available from ExxonMobil. The information and recommendations are offered for the user's consideration and



Product Name: MOBIL DELVAC EXTENDED LIFE 50/50 PREDILUTED COOLANT/ANTIFREEZE  
Revision Date: 13 May 2020  
Page 11 of 11

---

examination. It is the user's responsibility to satisfy itself that the product is suitable for the intended use. If buyer repackages this product, it is the user's responsibility to insure proper health, safety and other necessary information is included with and/or on the container. Appropriate warnings and safe-handling procedures should be provided to handlers and users. Alteration of this document is strictly prohibited. Except to the extent required by law, republication or retransmission of this document, in whole or in part, is not permitted. The term, "ExxonMobil" is used for convenience, and may include any one or more of ExxonMobil Chemical Company, Exxon Mobil Corporation, or any affiliates in which they directly or indirectly hold any interest.

---

Internal Use Only

MHC: 2, 0, 0, 0, 0, 0

PPEC: C

DGN: 7074341XUS (1011503)

---

Copyright 2002 Exxon Mobil Corporation, All rights reserved

25062519m02 2021